

TACTILE TERRACED STAINLESS STEEL (316)



TACTILE GROUND SURFACE INDICATOR

RANGE	Stainless Terraced
TYPE	Warning Tactile
MATERIAL	316 marine grade stainless steel
FINISH	Machined
DIMENSIONS	OUTER DIA: 35mm TOP DIA: 25mm THICKNESS: 5mm SHAFT: M6mm x 18mm

FEATURES

Machined, concentric circle design on the horizontal face with a terraced slip resistant outer edge

Tested for compliance with AS/NZS 1428.4

Tested for compliance with the BCA Section D clause 3.8 (TGSIs)

Tested for compliance with slip resistance requirements as detailed in HB 197

2 year product warranty

SLIP RESISTANCE TESTING

Important information: To determine a classification of a slip resistance rating, see Australian Standards Hand Book 197 (HB 197), an Introductory Guide to Slip Resistance of Pedestrian Materials. This document outlines the minimum ratings of a location and situation of a pedestrian surface.

TEST	AS/NZS 4586 APPENDIX A
TYPE	Wet Pendulum Test
RATING 1	Four S Slider = 70
RATING 2	TRRL Slider = 43
CLASS	Mean BPN = Class V
REPORT	(Intertile Pty Ltd test report) Available on request from DTAC

LUMINANCE TESTING

Important information: To determine a luminance contrast between a substrate and the DTAC TGSIs node, see: AS/NZS 1428.4, page 51-59, Appendix F. DTAC can test your substrate for luminance contrast to give you peace of mind that your DTAC project will be fully compliant to AS/NZS 1428.4.

TEST	AS/NZS 1428.4 APPENDIX F
TYPE	Access for people with disabilities
CLASS	Luminance Reflectance rating = Dry = 19.9/Wet = 19.9
REPORT	(CSIRO test report 2756-5, 6 & 7B) Available on request from DTAC

DTAC PTY LTD
ABN 41 093 070 127

Unit 4, 11-12 Phillip Court
Port Melbourne Victoria
Australia 3207

T 1300 793 478
F 1300 780 628

PO Box 5059
South Melbourne Victoria
Australia 3205


estimating@dtac.com.au
www.dtac.com.au

© DTAC Pty Ltd 2012

INSTALLATION - TERRACED STAINLESS STEEL (316)

TYPE 1 SUBSTRATES


STONE, MASONRY, TIMBER, VINYL



CODE DT0110

FIXING Drill and pressure fit

NOTE Any thick substrate where maximum hold is required without chemical anchoring




CODE DT0131

FIXING Drill and glue

NOTE To be used to avoid anchoring obstacles (grout lines, expansion joints etc) in thick, drillable substrate

TYPE 2 SUBSTRATES


VITRIFIED PORCELAIN, CERAMICS, GLASS, METALS



CODE DT0111

FIXING Direct stick

NOTE Any thick or thin non drillable substrate




CODE DT0110

FIXING Diamond core/pressure fit

NOTE Any thick or thin non drillable substrate where maximum hold is required

TYPE 3 SUBSTRATES


CARPET, CARPET TILES



CODE DT0116

FIXING Drill and screw

NOTE Thick carpet with underlay (broad loom/natural sisal carpets). Two stage installation process



CODE DT0113

FIXING Drill and screw

NOTE Thin carpet without underlay (direct stick carpet/carpet tiles). Two stage installation process