

TACTILE CLASSIC LIGHT GREY POLYRESIN



TACTILE GROUND SURFACE INDICATOR

RANGE	Polyresin Classic
TYPE	Warning Tactile
MATERIAL	Light grey virgin and re-claimed UV and thermally stabilized high impact elastomeric based polymer
FINISH	Machined
DIMENSIONS	OUTER DIA: 35mm TOP DIA: 25mm THICKNESS: 5mm SHAFT: M6mm x 20mm

FEATURES

Moulded, concentric circle design on the horizontal face with a smooth outer edge

Tested for compliance with AS/NZS 1428.4

Tested for compliance with the BCA Section D clause 3.8 (TGSIs)

Tested for compliance with slip resistance requirements as detailed in HB 197

2 year product warranty

SLIP RESISTANCE TESTING

Important information: To determine a classification of a slip resistance rating, see Australian Standards Hand Book 197 (HB 197), an Introductory Guide to Slip Resistance of Pedestrian Materials. This document outlines the minimum ratings of a location and situation of a pedestrian surface.

TEST	AS/NZS 4586 APPENDIX A
TYPE	Wet Pendulum Test
RATING 1	Four S Slider = 46
RATING 2	TRRL Slider = 36
CLASS	Mean BPN = Class N/A
REPORT	(Intertile Pty Ltd test report) Available on request from DTAC

DTAC PTY LTD
ABN 41 093 070 127

Unit 4, 11-12 Phillip Court
Port Melbourne Victoria
Australia 3207

T 1300 793 478
F 1300 780 628

PO Box 5059
South Melbourne Victoria
Australia 3205


estimating@dtac.com.au
www.dtac.com.au

© DTAC Pty Ltd 2012

INSTALLATION - CLASSIC LIGHT GREY POLYRESIN

TYPE 1 SUBSTRATES

STONE, MASONRY, TIMBER, VINYL




CODE DT0600LG

FIXING Drill and pressure fit

NOTE Any thick substrate where maximum hold is required without chemical anchoring

TYPE 2 SUBSTRATES

VITRIFIED PORCELAIN, CERAMICS, GLASS, METALS




CODE DT0600LG

FIXING Diamond core/pressure fit

NOTE Any thick or thin non drillable substrate

TYPE 3 SUBSTRATES

CARPET, CARPET TILES



CODE DT0600LG

FIXING Drill and pressure fit

NOTE Thin carpet without underlay (direct stick carpet/carpet tiles). Two stage installation process