

TACTILE COLOURMAX BLACK STAINLESS STEEL (316)



TACTILE GROUND SURFACE INDICATOR

RANGE	Colourmax
TYPE	Directional Tactile
MATERIAL	316 marine grade stainless steel with an outer polymer ring
FINISH	Machined

FEATURES

Machined, grooved design on the horizontal face with a moulded outer polymer body

Tested for compliance with AS/NZS 1428.4

Tested for compliance with the BCA Section D clause 3.8 (TGSIs)

Tested for compliance with slip resistance requirements as detailed in HB 197

2 year product warranty

SLIP RESISTANCE TESTING

Important information: To determine a classification of a slip resistance rating, see Australian Standards Hand Book 197 (HB 197), an Introductory Guide to Slip Resistance of Pedestrian Materials. This document outlines the minimum ratings of a location and situation of a pedestrian surface.

TEST	AS/NZS 4586 APPENDIX A
TYPE	Wet Pendulum Test
RATING 1	Four S Slider = 34
CLASS	Mean BPN = Class N/A
REPORT	(Intertile Pty Ltd test report) Available on request from DTAC

LUMINANCE TESTING

Important information: To determine a luminance contrast between a substrate and the DTAC TGS node, see: AS/NZS 1428.4, page 51-59, Appendix F. DTAC can test your substrate for luminance contrast to give you peace of mind that your DTAC project will be fully compliant to AS/NZS 1428.4.

TEST	AS/NZS 1428.4 APPENDIX F
TYPE	Access for people with disabilities
CLASS	Luminance Reflectance rating = Dry - 29.7/Wet = 36.1
REPORT	(CSIRO test report 2756-5, 6 & 7B) Available on request from DTAC

DTAC PTY LTD
ABN 41 093 070 127

Unit 4, 11-12 Phillip Court
Port Melbourne Victoria
Australia 3207

T 1300 793 478
F 1300 780 628

estimating@dtac.com.au
www.dtac.com.au


PO Box 5059
South Melbourne Victoria
Australia 3205

© DTAC Pty Ltd 2012

INSTALLATION - COLOURMAX BLACK STAINLESS STEEL (316)

TYPE 1 SUBSTRATES

STONE, MASONRY, TIMBER, VINYL




CODE DIRC0502B

FIXING Diamond core

NOTE Any thick substrate

TYPE 2 SUBSTRATES

VITRIFIED PORCELAIN, CERAMICS, GLASS, METALS



CODE DIRC0502B

FIXING Diamond core

NOTE Any thick substrate

3 AVAILABLE LENGTHS


CODE DIRC0502B

SIZE L100 x W35 x H5mm




CODE DIRC0503B

SIZE L165 x W35 x H5mm



CODE DIRC0505B

SIZE L290 x W35 x H5mm



Available in 3 sizes to conform to the precise installation requirements that vary from one application to the next so as to ensure a safe and accessible path for all pedestrians. 'H' indicates height above surface.