

BRONZE RIBBED TEST RESULTS



TACTILE GROUND SURFACE INDICATOR (DISCRETE)

RANGE	Bronze Ribbed
GROUP	Warning Tactile
MATERIAL	Extruded bronze
FINISH	Mill finish
SUBSTRATE	As to particular product/substrate type recommendation
FIXING	As to particular method for product/substrate type recommendation

FEATURES

Engraved, concentric circle design on horizontal face with ribbed slip resistant beveled edge

Manufactured in Australia from extruded solid 316 marine grade stainless steel

Unique integrated 'HEX' shaft design for substrate mounting (patents and design registrations applied and granted)

Tested for compliance with AS/NZS 1428.4: (1992 & 2002)

Tested for compliance with the BCA Section D clause 3.8 (TGSIs)

Tested for compliance with slip resistance requirements as detailed in HB 197 (1999)

10 year product warranty with option to extend. All installations are covered by a *Statement of Compliance* and a 24 month installation guarantee signed by a DTAC director

DTAC's facility to reclaim, recycle and reinstate

SLIP RESISTANCE TESTING

Important information about slip resistance ratings: To determine a classification of a slip resistance rating, see Australian Standards Hand Book 197: 1999 (HB 197), An Introductory Guide to Slip Resistance of Pedestrian Materials. This document outlines the minimum ratings of a location and situation of a pedestrian surface.

TEST	AS/NZS 4586:1999 APPENDIX A
TYPE	Wet Pendulum Test
RATING 1	Four S Slider = 56
RATING 2	TRRL Slider = 33
CLASS	Mean BPN = Class V
REPORT	(CSIRO test report 2352-1s) Available on request from DTAC

LUMINANCE TESTING

Important information: To determine a luminance contrast between a substrate and the DTAC TGS node, see: AS/NZS 1428.4 2002, page 51-59, appendix F.

TEST	AS 1428:4 2002 APPENDIX F
TYPE	Access for people with disabilities
RATING	Luminance Reflectance rating = Dry = 27.1/ Wet = 28.1
REPORT	(CSIRO test report 2756-5, 6 & 7B) Available on request from DTAC

MELBOURNE
SYDNEY

CANBERRA
BRISBANE
ADELAIDE

PERTH
DARWIN
HOBART

DTAC PTY LTD
ABN 41 093 070 127

Unit 4, 1-7 Friars Road
Moorabbin Victoria
Australia 3189
PO Box 2210
Moorabbin Victoria
Australia 3189

T 1300 793 478
F 1300 780 628
estimating@dtac.com.au
www.dtac.com.au

BRONZE RIBBED INSTALLATION

DTAC PTY LTD
ABN 41 093 070 127

Unit 4, 1-7 Friars Road
Moorabbin Victoria
Australia 3189
PO Box 2210
Moorabbin Victoria
Australia 3189


T 1300 793 478
F 1300 780 628
estimating@dtac.com.au
www.dtac.com.au

TYPE 1 SUBSTRATES

STONE, MASONRY, TIMBER, VINYL




CODE AST-BNZ-7.5x8.0-RT
FIXING Drill and glue
NOTE Any thin drillable substrate such as timber or thin stone



CODE AST-BNZ-8x18-RT-PF
FIXING Drill and pressure fit
NOTE Any thick substrate where maximum hold is required without chemical anchoring


GREEN 100% recyclable, no adhesives




CODE AST-BNZ-M6x16-HEX-OC
FIXING Drill and glue
NOTE To be used to avoid anchoring obstacles (grout lines, expansion joints etc) in thick, drillable substrate

TYPE 2 SUBSTRATES

VITRIFIED PORCELAIN, CERAMICS, GLASS, METALS



CODE AFT-BNZ
FIXING Direct stick
NOTE Any thin or thick non drillable substrate




CODE AST-BNZ-8x18-RT-PF
FIXING Diamond core/pressure fit
NOTE Any thin or thick non drillable substrate where maximum hold is required without chemical anchoring

GREEN 100% recyclable, no adhesives


TYPE 3 SUBSTRATES

CARPET, CARPET TILES



CODE ASCT-BNZ-6.0-HEX
FIXING Drill and screw
NOTE Thick carpet with underlay (broad loom/natural sisal carpets). Two stage installation process

GREEN 100% recyclable, no adhesives



CODE ASCT-BNZ-3.0-HEX
FIXING Drill and screw
NOTE Thin carpet without underlay (direct stick carpet/carpet tiles). Two stage installation process

GREEN 100% recyclable, no adhesives