

POLYRESIN CLASSIC LIGHT GREY – SILVER TOP TEST RESULTS



TACTILE GROUND SURFACE INDICATOR (DISCRETE)

| | |
|------------------|---|
| RANGE | Polyresin Classic |
| GROUP | Warning Tactile |
| MATERIAL | Light grey virgin and re-claimed UV and thermally stabilized high impact elastomeric based polymers |
| FINISH | Mill finish |
| SUBSTRATE | As to particular product/substrate type recommendation |
| FIXING | As to particular method for product/substrate type recommendation |

FEATURES

Silver polymer insert with engraved, concentric circle design on horizontal face with light grey body and smooth outer edge

Manufactured in Australia from virgin and re-claimed UV and thermally stabilized high impact elastomeric based polymers

Unique integrated 'HEX' shaft design for substrate mounting (patents and design registrations applied and granted)

Tested for compliance with AS/NZS 1428.4: [1992 & 2002]

Tested for compliance with the BCA Section D clause 3.8 [TGSIs]

Tested for compliance with slip resistance requirements as detailed in HB 197 (1999)

5 year on polymer for colour stability (polymer), 2 year installation warranty

DTAC's facility to reclaim, recycle and reinstate

SLIP RESISTANCE TESTING

Important information about slip resistance ratings: To determine a classification of a slip resistance rating, see Australian Standards Hand Book 197: 1999 (HB 197), An Introductory Guide to Slip Resistance of Pedestrian Materials. This document outlines the minimum ratings of a location and situation of a pedestrian surface.

| | |
|-----------------|--|
| TEST | AS/NZS 4586:1999 APPENDIX A |
| TYPE | Wet Pendulum Test |
| RATING 1 | Four S Slider = 46 |
| RATING 2 | TRRL Slider = 36 |
| CLASS | Mean BPN = Class N/A |
| REPORT | (Intertile Pty Ltd test report) Available on request from DTAC |

LUMINANCE TESTING

Important information: To determine a luminance contrast between a substrate and the DTAC TGS node, see: AS/NZS 1428.4 2002, page 51-59, appendix F. As the testing for luminance is performed only on the 25mm face of the TGS (test report), INSAFE product IS-AS-PL-SILVER has been applied to this product. The colour of the disc insert (25mm) would fall within the mean luminance rating.

| | |
|---------------|---|
| TEST | AS 1428:4 2002 APPENDIX F |
| TYPE | Access for people with disabilities |
| RATING | Luminance Reflectance rating / Mean TBA |
| REPORT | [Test report N/A] |

| | | |
|---|--|---|
| MELBOURNE SYDNEY | CANBERRA BRISBANE ADELAIDE | PERTH DARWIN HOBART |
| DTAC PTY LTD ABN 41 093 070 127 | Unit 4, 1-7 Friars Road Moorabbin Victoria Australia 3189 PO Box 2210 Moorabbin Victoria Australia 3189 | T 1300 793 478 F 1300 780 628 estimating@dtac.com.au www.dtac.com.au |

POLYRESIN CLASSIC LIGHT GREY – SILVER TOP INSTALLATION


DTAC PTY LTD
ABN 41 093 070 127

Unit 4, 1-7 Friars Road
Moorabbin Victoria
Australia 3189
PO Box 2210
Moorabbin Victoria
Australia 3189

T 1300 793 478
F 1300 780 628
estimating@dtac.com.au
www.dtac.com.au

TYPE 1 SUBSTRATES

STONE, MASONRY, TIMBER, VINYL



CODE BS-PL-M8x18-HEX-PF-
LIGHTGREY-SILVER


FIXING Drill and pressure fit

NOTE Any thick substrate where
maximum hold is required
without chemical anchoring

GREEN 100% recyclable, no adhesives

TYPE 2 SUBSTRATES

VITRIFIED PORCELAIN, CERAMICS, GLASS, METALS



CODE BS-PL-M8x18-HEX-PF-
LIGHTGREY-SILVER


FIXING Diamond core/pressure fit

NOTE Any thick substrate where
maximum hold is required
without chemical anchoring

GREEN 100% recyclable, no adhesives

TYPE 3 SUBSTRATES

CARPET, CARPET TILES



CODE BS-PL-M8x18-HEX-PF-
LIGHTGREY-SILVER

FIXING Drill and pressure fit

NOTE Thin carpet without underlay
(direct stick carpet/carpet tiles).
Two stage installation process

GREEN 100% recyclable, no adhesives