

# TACTILE CLASSIC YELLOW POLYRESIN



## TACTILE GROUND SURFACE INDICATOR

RANGE	Polyresin Classic
TYPE	Warning Tactile
MATERIAL	Yellow virgin and re-claimed UV and thermally stabilized high impact elastomeric based polymer
FINISH	Machined
DIMENSIONS	OUTER DIA: 35mm TOP DIA: 25mm THICKNESS: 5mm SHAFT: M6mm x 20mm

## FEATURES

Moulded, concentric circle design on the horizontal face with a smooth outer edge

Tested for compliance with AS/NZS 1428.4

Tested for compliance with the BCA Section D clause 3.8 (TGSIs)

Tested for compliance with slip resistance requirements as detailed in HB 197

2 year product warranty

## SLIP RESISTANCE TESTING

Important information: To determine a classification of a slip resistance rating, see Australian Standards Hand Book 197 (HB 197), an Introductory Guide to Slip Resistance of Pedestrian Materials. This document outlines the minimum ratings of a location and situation of a pedestrian surface.

TEST	AS/NZS 4586 APPENDIX A
TYPE	Wet Pendulum Test
RATING 1	Four S Slider = 46
RATING 2	TRRL Slider = 36
CLASS	Mean BPN = Class N/A
REPORT	(Intertile Pty Ltd test report) Available on request from DTAC

## LUMINANCE TESTING

Important information: To determine a luminance contrast between a substrate and the DTAC TGSIs node, see: AS/NZS 1428.4, page 51-59, Appendix F. DTAC can test your substrate for luminance contrast to give you peace of mind that your DTAC project will be fully compliant to AS/NZS 1428.4.

TEST	AS/NZS 1428.4 APPENDIX F
TYPE	Access for people with disabilities
RATING	Luminance Reflectance rating = Dry = 23.5 / Wet = 19.66 / Mean = 10.2-34.1
REPORT	(CSIRO test report 3380 L) Available on request from DTAC

DTAC PTY LTD  
ABN 41 093 070 127

Unit 4, 11-12 Phillip Court  
Port Melbourne Victoria  
Australia 3207

T 1300 793 478  
F 1300 780 628

PO Box 5059  
South Melbourne Victoria  
Australia 3205


estimating@dtac.com.au  
www.dtac.com.au

© DTAC Pty Ltd 2012

# INSTALLATION - CLASSIC YELLOW POLYRESIN

## TYPE 1 SUBSTRATES

STONE, MASONRY, TIMBER, VINYL




**CODE** DT0600Y

**FIXING** Drill and pressure fit

**NOTE** Any thick substrate where maximum hold is required without chemical anchoring

## TYPE 2 SUBSTRATES

VITRIFIED PORCELAIN, CERAMICS, GLASS, METALS




**CODE** DT0600Y

**FIXING** Diamond core/pressure fit

**NOTE** Any thick or thin non drillable substrate

## TYPE 3 SUBSTRATES

CARPET, CARPET TILES



**CODE** DT0600Y

**FIXING** Drill and pressure fit

**NOTE** Thin carpet without underlay (direct stick carpet/carpet tiles). Two stage installation process