

TACTILE CLASSIC STAINLESS STEEL (316)



TACTILE GROUND SURFACE INDICATOR

RANGE	Stainless Classic
TYPE	Directional Tactile
MATERIAL	316 marine grade stainless steel
FINISH	Machined

FEATURES

- Machined, grooved design on the horizontal face with a smooth outer edge
- Tested for compliance with AS/NZS 1428.4
- Tested for compliance with the BCA Section D clause 3.8 (TGSIs)
- Tested for compliance with slip resistance requirements as detailed in HB 197
- 2 year product warranty, 2 year installation warranty

SLIP RESISTANCE TESTING

Important information: To determine a classification of a slip resistance rating, see Australian Standards Hand Book 197 (HB 197), an Introductory Guide to Slip Resistance of Pedestrian Materials. This document outlines the minimum ratings of a location and situation of a pedestrian surface.

TEST	AS/NZS 4586 APPENDIX A
TYPE	Wet Pendulum Test
RATING 1	Four S Slider = 34
CLASS	Mean BPN = Class N/A
REPORT	(Intertile Pty Ltd test report) Available on request from DTAC

LUMINANCE TESTING

Important information: To determine a luminance contrast between a substrate and the DTAC TGS node, see: AS/NZS 1428.4, page 51-59, Appendix F. DTAC can test your substrate for luminance contrast to give you peace of mind that your DTAC project will be fully compliant to AS/NZS 1428.4.

TEST	AS/NZS 1428.4 APPENDIX F
TYPE	Access for people with disabilities
CLASS	Luminance Reflectance rating = Dry - 29.7/Wet = 36.1
REPORT	(CSIRO test report 2756-5, 6 & 7B) Available on request from DTAC

DTAC PTY LTD
ABN 41 093 070 127

Unit 4, 11-12 Phillip Court
Port Melbourne Victoria
Australia 3207

PO Box 5059
South Melbourne Victoria
Australia 3205

T 1300 793 478
F 1300 780 628


estimating@dtac.com.au
www.dtac.com.au

© DTAC Pty Ltd 2012


INSTALLATION - CLASSIC STAINLESS STEEL (316)

TYPE 1 SUBSTRATES

STONE, MASONRY, TIMBER, VINYL




CODE DIR0102
FIXING Diamond core
NOTE Any thick substrate




CODE DIR0102
FIXING Drill and glue
NOTE Any thick substrate where maximum anchorage is required

TYPE 2 SUBSTRATES

VITRIFIED PORCELAIN, CERAMICS, GLASS, METALS




CODE DIR0102
FIXING Diamond core
NOTE Any thick substrate




CODE DIR0102
FIXING Drill and glue
NOTE Any thick substrate where maximum anchorage is required

3 AVAILABLE LENGTHS


CODE DIR0102
SIZE L100 x W35 x H5mm



CODE DIR0103
SIZE L165 x W35 x H5mm



CODE DIR0105
SIZE L290 x W35 x H5mm



Available in 3 sizes to conform to the precise installation requirements that vary from one application to the next so as to ensure a safe and accessible path for all pedestrians. 'H' indicates height above surface.