

# TACTILE CLASSIC STAINLESS STEEL (316)



## TACTILE GROUND SURFACE INDICATOR

RANGE	Stainless Classic
TYPE	Warning Tactile
MATERIAL	316 marine grade stainless steel
FINISH	Machined
DIMENSIONS	OUTER DIA: 35mm TOP DIA: 25mm THICKNESS: 5mm SHAFT: M6mm x 18mm

## FEATURES

Machined, concentric circle design on the horizontal face with a smooth outer edge  
Tested for compliance with AS/NZS 1428.4  
Tested for compliance with the BCA Section D clause 3.8 (TGSIs)  
Tested for compliance with slip resistance requirements as detailed in HB 197  
2 year product warranty

## SLIP RESISTANCE TESTING

Important information: To determine a classification of a slip resistance rating, see Australian Standards Hand Book 197 (HB 197), an Introductory Guide to Slip Resistance of Pedestrian Materials. This document outlines the minimum ratings of a location and situation of a pedestrian surface.

TEST	AS/NZS 4586 APPENDIX A
TYPE	Wet Pendulum Test
RATING 1	Four S Slider = 56
RATING 2	TRRL Slider = 33
CLASS	Mean BPN = Class V
REPORT	(Intertile Pty Ltd test report) Available on request from DTAC

TEST	AS/NZS 4586 APPENDIX C
TYPE	Wet/Barefoot Ramp Test
CLASS	Mean angle of inclination = 29 Class = C
REPORT	(Intertile Pty Ltd test report) Available on request from DTAC

TEST	AS/NZS 4586 APPENDIX D
TYPE	Oil/Wet Ramp Test
CLASS	Mean overall acceptance angle = 22.5 Class = R11
REPORT	(Intertile Pty Ltd test report) Available on request from DTAC

## LUMINANCE TESTING

Important information: To determine a luminance contrast between a substrate and the DTAC TGS node, see: AS/NZS 1428.4, page 51-59, Appendix F. DTAC can test your substrate for luminance contrast to give you peace of mind that your DTAC project will be fully compliant to AS/NZS 1428.4.

TEST	AS/NZS 1428.4 APPENDIX F
TYPE	Access for people with disabilities
CLASS	Luminance Reflectance rating = Dry = 29.7/Wet = 36.1
REPORT	(CSIRO test report 2756-5, 6 & 7B) Available on request from DTAC

DTAC PTY LTD  
ABN 41 093 070 127

Unit 4, 11-12 Phillip Court  
Port Melbourne Victoria  
Australia 3207

T 1300 793 478  
F 1300 780 628

estimating@dtac.com.au  
www.dtac.com.au


PO Box 5059  
South Melbourne Victoria  
Australia 3205

© DTAC Pty Ltd 2012

# INSTALLATION - CLASSIC STAINLESS STEEL (316)

## TYPE 1 SUBSTRATES


STONE, MASONRY, TIMBER, VINYL



**CODE** DT0100

**FIXING** Drill and pressure fit

**NOTE** Any thick substrate where maximum hold is required without chemical anchoring




**CODE** DT0130

**FIXING** Drill and glue

**NOTE** To be used to avoid anchoring obstacles (grout lines, expansion joints etc) in thick, drillable substrate

## TYPE 2 SUBSTRATES


VITRIFIED PORCELAIN, CERAMICS, GLASS, METALS



**CODE** DT0101

**FIXING** Direct stick

**NOTE** Any thick or thin non drillable substrate




**CODE** DT0100

**FIXING** Diamond core/pressure fit

**NOTE** Any thick or thin non drillable substrate where maximum hold is required

## TYPE 3 SUBSTRATES


CARPET, CARPET TILES



**CODE** DT0106

**FIXING** Drill and screw

**NOTE** Thick carpet with underlay (broad loom/natural sisal carpets). Two stage installation process



**CODE** DT0103

**FIXING** Drill and screw

**NOTE** Thin carpet without underlay (direct stick carpet/carpet tiles). Two stage installation process